

## >> Miscellaneous

### > Fill Stik

#### Aerosol PU foam

One component aerosol PU foam containing an environmentally safe propellant. Self expanding, moisture curing.

The foam can be overpainted, cut and perforated after curing. It is resistant to temperatures ranging from -40°C to +100°C and to ageing. Mould resistant.

The foam adheres to wood, concrete, plaster, brick, metal, plastics.

**Applications:** acoustic and thermal insulation. For filling wall and floor holes, for fastening of wooden door frames and assembling and sealing window frames, for insulating and filling gaps and other cavities, pipes and conduits in air-conditioning, heating and electrical installations.

**Packaging:** FILL-STICK 825 aerosol bomb 825 ml, about 40 l. foam. It can be used in any position. FILL-STICK 750 aerosol bomb 750 ml, about 40 l. foam. To be used with proper spray gun. FILL-STICK 750 RV aerosol bomb 750 ml, about 35 l. foam. To be used upside down.



### > Pulitore per Fill Stik

#### Cleaner for application gun

**Packaging:** tinplate container with adapter ring, 500 ml



### > Filtene

#### Polyethylene foam back-up spacer for joints.

Compressible closed cell foam, non-adhesive bond-breaker compatible with every kind of sealant. Round section.

**Size:** diameter 6,10,15,20,25,30,40,50 mm

### > Flashband

#### Bituminous self adhesive sealant.

Flexible and mouldable aluminium band coated with a bitumen based self adhesive layer.

Flashband can be applied both cold and hot to many substrates. It fits the joint shape or the surface to protect.

**Applications:** for coating iron sheeting, roof coverings, concrete ceilings. For repairing roof coverings, joints on roofs, gutters, skylights and greenhouses. For covering parapets and windowsills.

**Packaging:** 10 m. rolls - width from 5 to 70 cm.

**Colours:** Aluminium and graphite

